



DEVIlink™ CC

The DEVIlink™ CC (Central Controller) is the central brain in the DEVIlink™ system, which includes several wireless DEVIlink™ units installed around the building. The idea of the DEVIlink™ System is to link together your heating system wirelessly and control it from one central point.

The DEVIlink™ CC communicates wirelessly with all other DEVIlink™ units in the installation. A single DEVIlink™ CC can control up to 30 rooms and be connected up to totally 50 devices

Benefits:

- Central control of the entire house
- Minimize energy consumption
- Vacation mode
- Controlling of ON/OFF devices
- Weekly heating schedule

Standard compliance:

- The DEVIlink™ CC is in compliance with EN 60730 and EN 300 220-2.

Certificates:



Type	Value
Operation voltage	15 V DC ±10%
Standby power consumption	Max. 2 W
Screen	3.5" TFT colour w. touch
Ambient temperature	-10 to +40 °C
Storage temperature	-20 to +65 °C
Ball pressure test temperature	75 °C
Pollution degree	2 (domestic use)
Transmission frequency	868.42 MHz
Transmission range	Up to 30 m
Max. repeaters in a chain	3
Transmission power	Max. 1 mW
Software class	A
IP class	21
Dimensions	125 x 107 x 25 mm
Weight	179 g

Types

Item no.	Product name	Type	EAN no.
140F1076	DEVIlink™ CC with PSU	Permanent Installation	5703466232460
140F1077	DEVIlink™ CC with NSU	Supply by Plug	5703466232477

Accessories

Item no.	Product name	Type	EAN no.
014G0260	BSU DEVIlink™ CC / Danfoss Link CC	Battery Supply Unit	5702420110653
014G0261	PSU DEVIlink™ CC / Danfoss Link CC	Permanent Supply Installation	5702420110646
014G0262	NSU DEVIlink™ CC / Danfoss Link CC	Supply by Plug	5702420110639

DEVIlink™ system units

Item no.	Product name	Type	EAN no.
088U0230	RU DEVIlink™ / Danfoss Link	Repeater Unit	5702420068244
19190004	DEVIlink™ RS	Room sensor-Wireless -Battery Supply	5703466174432
088L1905	Danfoss Link™ FT	Floor Thermostat with ELKO frame	5703466174371
19190026	DEVIlink™ PR	Plug in Relay	5703466197271
19190027	DEVIlink™ HR	Hidden Relay	5703466197288