



## DEVIreg™ 130

The DEVIreg™ 130 is a simple electronic thermostat to be installed directly on the wall, using a floor sensor (wire) to measure and control the desired floor temperature.

The thermostat has a dial for adjusting the temperature setting with a scale from 1 to 5.

Furthermore, the thermostat has an LED indicating the current mode (heating, standby or fault).



### Benefits:


- Double pole safety breaker
- Sensor failure monitoring
- LED indication
- Frost protection

### Standard compliance:

- EN/IEC 60730-1 (general) and EN/IEC 60730-2-9 (thermostat)

### Approvals:



Type	Value
Operation voltage	220 V- 240V~ 50/60 Hz
Standby power consumption	Max. 5 W
Relay:	
Resistive load	Max 16A / 3680W @ 230V
Inductive load	Cos Φ = 0.3 max. 1A
Sensing unit	NTC 15 kOhm at 25° C
Hysteresis	± 0.2° C
Ambient temperature	-10° C. to +30° C
Frost protection	5° C - ❄️
Temperature range	5° C - 45° C
Cable specification max	1 x 4 mm <sup>2</sup> or 2 x 2,5 mm <sup>2</sup>
Ball pressure test temperature	75° C
Pollution degree	2 (domestic use)
Controller type	1 C
Storage temperature	-20° C to +65° C
IP class	30
Protection class	Class II - 
Dimensions (H/W/D)	82 mm x 82 mm x 36 mm
Weight	90 g

### Types

Item no.	Product name	Type	EAN no.
140F1010	DEVIreg™ 130	With floor sensor	5703466208953