

Schluter Ditra-Heat-E-R



DITRA-HEAT-E-R is a non-programmable digital thermostat used to control the DITRA-HEAT-E-HK heating cables (either 120 V or 240 V). The thermostat features a 5 mA built-in ground fault circuit interrupter (GFCI) with indicator light and includes a floor temperature sensor.

With a 2" (5.1 cm) touchscreen display for the time-controlled regulation of electrically heated floor and wall coverings with Schlüter®-DITRA-HEAT-E. The device can either be used exclusively to set the covering temperature or for temperature control with room air adjustment.

DITRA-HEAT-E-R is operated via a simple on/off switch. Two heating cables may be connected to the thermostat, up to the total heating load limit of 15 amps. The DITRA-HEAT-E-RR power module may be used in conjunction with the thermostat when the heating load exceeds 15 amps (e.g., in large floor applications) to maintain a single point of control.

Benefits:

- Digital display with backlit screen
- Simple on/off operation
- Supports 120V and 240V cables
- 5 mA built-in GFCI
- Floor temperature sensor included
- 3-year warranty

Technical Specification	
Supply:	120/240 Vac
Load:	Max. 15A (resistive load)
Power:	1,800 W at 120 Vac 3,120 W at 208 Vac 3,600 W at 240 Vac
GFCI:	Class A (5 mA trip level)
Floor sensor:	NTC 10K Ω @ 25°C

Stock Code	Product Name	Voltage
S_DHE_RT_103/BW	Schluter Ditra-Heat-E-R	120

